



## TECHNICAL SHEET

### LUB-OXI-2

**LUB-OXI-2**, is a concentrated passivator deoxidizer for general use, which acts by contact, conditioning the metal while it exerts its deoxidizing action, removing rust, stains, carbon, etc. and leaving the surface smooth and clean. **LUB-OXI-2**, has been formulated based on Phosphoric Acid, surfactants, chemical and inert solvents. **LUB-OXI-2**, comes in two presentations **LUB-OXI-2**, and **LUB-OXI-2-ENG**, being the latter of greater concentration and deoxidizing power.

### ADVANTAGES AND PROPERTIES

- **LUB-OXI-2**, is a concentrated product with great deoxidizing power
- Can be used pure or diluted in water
- It is easy to apply and handle
- It can be applied on any surface that needs to be deoxidized.

### APPLICATIONS

It can be applied to iron sheets, pipes, machines exposed to the elements, valves, automobile parts and industry in general.

### APPLICATION

**LUB-OXI-2**, can be used pure or diluted depending on the amount of dirt to be removed. It can be applied by brush, brush, sponge or by immersion. Once the piece has been deoxidized, it must be rinsed with plenty of water. If a longer lasting anti-corrosion protection is desired, the treated part must be cured with neutral oil or use an anti-corrosion protector. **LUB-PROTEC-2**, to guarantee long periods of storage, without new oxidation being observed. **LUB-OXI-2-ENG**, it must be applied by internal circulations and its amount will depend on the amount of carbonates to be removed

### PROPERTIES PHYSICO-CHEMICAL

	<b>LUB-OXI-2</b>	<b>LUB-OXI-2 ENG</b>
<b>COLOR:</b>	Colorless / Light Yellow	Colorless/ Light Yellow
<b>ASPECT</b>	Liquid	Liquid
<b>APPARENT VISCOSITY, cps</b>	15 - 30	25 - 45
<b>SPECIFIC GRAVITY, at 25°C</b>	1,080 - 1,090	1,235 - 1,265
<b>1% pH</b>	3 max	3 max
<b>SOLUBILITY</b>	100% in Water	100% in Water

### INFORMATION

#### ENVIRONMENTAL

Handle as an industrial chemist, wear personal protective equipment. See precautionary measures in the SAFETY DATA SHEET

### DRIVING SURE

### PRESENTATION



**LUB-OXI-2**, is dispatched in 208 Lt drums, pailas or 19 Lt buckets. The product can be stored up to 12 months.