



Waterproofing Harmony (Rubber-Elastomeric) ARM-597 LINE

PRODUCT DATA SHEET

GENERAL DATA

Product description:	It is a Premium quality water-based waterproofing product, made with high-quality raw materials such as elastomeric resins, pigments and special additives formulated to form a waterproof film and durability superior to that of the asphalt-based mantle, thus avoiding leak problems. Moisture due to roof leaks. It is ecological since it does not contain asphalt or its derivatives.
Recommended Use:	It is recommended on concrete and masonry surfaces in general
Color:	White, Red and Green
Film Appearance:	Mate.
Percent Solids	By volume: 60 ±2%.
Theoretical performance:	(65m ² /gallon at 25 microns (1 mils)) Not
Recommended finish:	Applicable.
film thickness recommended	2 coats minimum (8-10 mils total)

SURFACE PREPARATION

General:	The surface must be clean, dry, free of grease, moisture, fungus or other contaminants. All traces of old or poorly adhered paint must be removed. The surface must ensure that the product has good penetration and adhesion.
-----------------	--

APPLICATION METHOD

General:	It is applied with a brush, roller, soft bristle brush, conventional spray gun. Apply a first coat of the product with a 10% dilution of water to seal the surface. It is recommended for a better performance to add two coats as a minimum, the second coat to be applied undiluted. Layers should be applied crisscross. You must ensure that the application is uniform and that there are no uncoated areas, you must take special care in critical points such as corners and cornices.
-----------------	---

September 2011

The data provided here is true. They are based on our best quality control and technical knowledge and are subject to change without notice. These data do not imply or express any type of guarantee for improper operational and/or interpretation management, as well as yields, performances or damages resulting from its application and use. The responsibility of PINTURAS FLAMUKO CA is limited only to the replacement of its products. The guarantee of the products of PINTURAS FLAMUKO CA reaches only its quality in the original container according to the Assurance and Quality Control of the company. Users must contact PINTURAS FLAMUKO CA to verify the correct use of our products before specifying and/or using them.

**Waterproofing Harmony
(Rubber - Elastomeric)
ARM-597 LINE**

MIXING AND DILUTION

Mixing Ratio Mixture Usage Time (Pot Life):	Does not apply.
Dilution:	Does not apply. Maximum 10% with water for the first

CLEANLINESS AND SAFETY

Cleaning:	Use soap and water.
Precautions:	Store in a cool, well-ventilated place. Keep tightly covered after use. Toxic product. Keep out of the reach of children.
Flashpoint:	Does not apply.

DRYING TIME

General:	These times are based on a temperature of 25°C (77°F), they can vary depending on the environmental conditions during the application and the thickness of the applied film. Avoid painting when rain is forecast.
Touch:	Four (04) Hours
repainted:	12 hours.
Hard:	Twenty four (24) Hours

PRESENTATION AND STORAGE

Presentation:	Gallon Container (3,785 Liters) and Cuñete, 5 gallons (18,925 Liters). Other packaging on request.
Storage Time: Storage Temperature and Humidity:	Twelve (12) months in well ventilated places. Maximum: 100°F (38°C) and 85% Relative Humidity.



Made in Venezuela by PINTURAS FLAMUKO CA
El Tigre Industrial Zone, Principal Av., Shed H. Guacara, Edo. Carabobo, Venezuela.
Telephones: (0245) 4000-400. Email: servicio.tecnico@pflamuko.com

September 2011

The data provided here is true. They are based on our best quality control and technical knowledge and are subject to change without notice. These data do not imply or express any type of guarantee for improper operational and/or interpretation management, as well as yields, performances or damages resulting from its application and use. The responsibility of PINTURAS FLAMUKO CA is limited only to the replacement of its products. The guarantee of the products of PINTURAS FLAMUKO CA reaches only its quality in the original container according to the Assurance and Quality Control of the company. Users must contact PINTURAS FLAMUKO CA to verify the correct use of our products before specifying and/or using them.